



Sixteen-drum locker with optional steel ramp simplifies drum loading.

## Outdoor Safety Lockers – Non-Combustible NEW


Safe, secure storage for flammables and hazardous chemicals

- Leakproof, all welded sump with galvanized steel grate flooring.
- 42-in (1.07-m) wide steel door system with 3-point lock.
- Chemical and UV resistant coating, inside and out.

Protect people and the environment and meet insurance requirements by storing hazardous materials in rugged, FM-approved Outdoor Safety Lockers. Non-combustible construction with heavy gauge steel and built-in secondary containment, every locker is fully compliant to meet EPA 40 CFR, NFPA 30 and NFPA 1 regulations. Proper chemical storage reduces poison hazards and accidents, minimizes contamination of chemicals, and prevents unwanted, costly fines.

Each locker features natural draft ventilation, NFPA 704 diamond decal for content identification, anchoring plates for hold down protection, and multiple static grounding connections for maximum safety. Forklift channels permit easy relocation.

Choose explosion relief panels for the storage of highly volatile Class 1A or dispensing of Class 1 A and 1B flammables as defined by NFPA – always check with the local authority having jurisdiction to ensure safety by following all local regulations, including proper setback requirements.



1. Air vents on both sides
2. Inside grounding lug
3. Leakproof sump with removable, galvanized steel grate floor
4. High visibility safety strip
5. Forklift channels
6. 3-point latching system
7. Outside grounding lug and anchor plate
8. Explosion relief design with blow-out panels



**For added convenience and safety . . .**  
Include ramp, shelving, grounding kit, fire protection and more – see page 44-45 for optional accessories.

**Global Protection**  
Justrite products are available worldwide. For pricing and availability, simply contact the authorized distributor nearest you.



**NON-COMBUSTIBLE** OUTDOOR SAFETY LOCKERS



55-Gal Drum Capacity	Sump Capacity Gallons/Liters	Dimensions W x D x H		Approv/Lstg Regulation	Standard		Explosion Relief	
		Exterior*	Interior		Model No	Ship Wt lb/kg	Model No	Ship Wt lb/kg
2	120/454	67 in x 38 in x 75 in 1702 mm x 965 mm x 1905 mm	54 in x 30 in x 55.5 in 1372 mm x 762 mm x 1410 mm	FM,N,A,E	911020	982/445	911021	1069/485
4	100/379	67 in x 62 in x 75 in 1702 mm x 1575 mm x 1905 mm	54 in x 54 in x 62 in 1372 mm x 1372 mm x 1575 mm		911040	1341/608	911041	1428/648
6	140/530	91 in x 62 in x 97 in 2311 mm x 1575 mm x 2464 mm	78 in x 54 in x 84 in 1981 mm x 1372 mm x 2134 mm		911060	1658/752	911061	1745/792
9	198/750	91 in x 86 in x 97 in 2311 mm x 2184 mm x 2464 mm	78 in x 78 in x 84 in 1981 mm x 1981 mm x 2134 mm		911090	2101/953	911091	2203/999
12	253/958	84 in x 115 in x 97 in 2134 mm x 2921 mm x 2464 mm	78 in x 102 in x 84 in 1981 mm x 2591 mm x 2134 mm		911120	2442/1108	911121	2616/1187
16	326/1234	115 in x 110 in x 97 in 2921 mm x 2794 mm x 2464 mm	102 in x 102 in x 84 in 2591 mm x 2591 mm x 2134 mm		911160	2959/1342	911161	3126/1418

Note: Door height on 2- and 4-drum models is 51-in (1.30-m) high and 80-in (2.03-m) high on 6- through 16-drum models. \*Dimensions include mounting plates and door hardware. In most instances, locker sizes 2- through 6-drum are available to ship via a closed container truck, which can potentially reduce freight costs as compared to flat bed shipping alternatives.



Six-drum locker with 42-in (1.07-m) wide steel door allows easy access to contents. Shown with optional ramp


## Outdoor Safety Lockers—Agri-Turf™ **NEW**

Designed for the safe and secure storage of agricultural and turf management chemicals

- Galvanized steel shelving provides extra storage space.
- R-11 insulation in walls, ceiling and sump walls for temperature control—available on select models.
- GFI receptacle with weatherproof cover.

Safely store herbicides, fungicides, pesticides, fertilizers and other agri-chemicals in these FM-approved lockers. Durable heavy-duty steel construction plus chemical and UV resistant green coating, inside and out, ensure long life. Natural draft ventilation, multiple static grounding connections and vapor-resistant exterior light with photocell promote safe storage and handling practices. Galvanized steel grate flooring along with leakproof secondary containment provide safe and quick cleanup. Use the convenient forklift channels for easy relocation. Each locker is fully compliant to meet EPA, NFPA 30 and NFPA 1 regulations.

Models with capacities 205 cubic feet (5.8 cubic meter) and larger also include a dust-proof interior light with weatherproof switch. Optional accessories for added convenience and safety include a loading ramp, grounding kit, fire protection, and heating and cooling packages.



Dust proof interior light on sizes 205 cu. ft. and larger



R-11 insulation in walls, ceiling, and sump walls



3-tier shelving (total 9 shelves) on sizes 205 cu. ft. and larger



Vapor-resistant exterior light with photocell



Weatherproof GFI receptacle and light switch



914060  
6-drum capacity



Capacity Cubic Feet/ Meters	Sump Capacity Gallons/Liters	Dimensions W x D x H		Approv/Lstg Regulation	Model No	Ship Wt lb/kg	Shelf** Qty	Interior Light & R-11 Insulation
		Exterior*	Interior					
52/1.5	91/345	67 in x 38 in x 75 in 1702 mm x 965 mm x 1905 mm	54 in x 30 in x 55.5 in 1372 mm x 762 mm x 1410 mm	FM,N,A,E	914020	1428/648	2	No
105/3.0	82/310	67 in x 62 in x 75 in 1702 mm x 1575 mm x 1905 mm	54 in x 54 in x 62 in 1372 mm x 1372 mm x 1575 mm		914040	1915/867	2	No
205/5.8	118/447	91 in x 62 in x 97 in 2311 mm x 1575 mm x 2464 mm	78 in x 54 in x 84 in 1981 mm x 1372 mm x 2134 mm		914060	2631/1193	9	Yes
296/8.4	171/647	91 in x 86 in x 97 in 2311 mm x 2184 mm x 2464 mm	78 in x 78 in x 84 in 1981 mm x 1981 mm x 2134 mm		914090	3355/1522	9	Yes
387/11.0	223/844	84 in x 115 in x 97 in 2134 mm x 2921 mm x 2464 mm	78 in x 102 in x 84 in 1981 mm x 2591 mm x 2134 mm		914120	3960/1796	9	Yes
506/14.3	292/1106	115 in x 110 in x 97 in 2921 mm x 2794 mm x 2464 mm	102 in x 102 in x 84 in 2591 mm x 2591 mm x 2134 mm		914160	4723/2142	9	Yes

Note: Door height on 52- and 105-cu ft models is 51-in (1.30-m) high and 80-in (2.03-m) high on 205- through 506-cu ft models.

\*Dimensions include mounting plates and door hardware. For exterior light and GFI receptacle add: 7-inch (178-mm) to W on 52- and 105-cu ft models; 3-inch (76-mm) to W and 6-inch (152-mm) to D on 205-, 296-, and 506-cu ft models; 6-inch (152-mm) to W and 5-inch (127-mm) to D on 387-cu ft model.

\*\*Shelves for 52- and 105-cu ft lockers are two-tier and back wall only. All other locker sizes have three-tier on back and side walls.

In most instances, locker sizes 52- through 205-cu ft are available to ship via a closed container truck, which can potentially reduce freight costs as compared to flat bed shipping alternatives.



Six-drum locker with optional ramp offers a convenient way to load or unload heavy drums using a drum dolly.

## Outdoor Safety Lockers—2-hour Fire-Rated NEW

*Fire-rated construction for safe storage of drums of flammables and combustibles*

- 90-minute fire-rated door—third party tested and labeled.
- Gravity air flow vents—UL Listed fire dampers with fusible links.

Manufactured with fire-rated and weatherproof construction, each 2-hour locker has an FM-approved fire-rated wall and roof design and meets EPA 40 CFR, NFPA 30 and NFPA 1 regulations. Multiple layers of fire-resistant gypsum wall board are encased between exterior heavy gauge steel and interior galvanized sheet steel for maximum durability. A leakproof, all welded sump provides compliant secondary containment of hazardous liquids. Galvanized steel grate flooring removes easily for cleaning.

Gravity air flow vents include UL Listed fire dampers and fusible links for maximum safety. Hydraulic door mechanism ensures door will automatically close. Forty-two inch (1.07-m) wide door comes with UL Listed keyed lockset for security. Additional safety features include static grounding connections, anchoring plates, and NFPA 704 diamond decal.

Designed to be placed near existing structures and/or property set-backs, 2-hour fire-rated lockers provide a safe yet convenient storage solution. This improved proximity advantage over non-combustible lockers allows for more efficient use, distribution and storage of your flammables and combustibles. NOTE: Please check with your local authority having jurisdiction for set-back requirements and the correct wall/roof rating needed for your application.

Lockers are also available with FM-approved explosion relief panels that release at 20 psf to reduce the damage associated with a potential explosion.



Independently tested and approved 90-minute fire-rated door



UL Listed air flow vent



Hydraulic door closer



### Customize your locker . . .

For specific applications with optional features and accessories, including loading ramp, shelving, grounding kit, fire protection, lighting, and heating/cooling packages—see pages 44-45.



55-Gal. Drum Capacity	Sump Capacity Gallons/Liters	Dimensions W x D x H		Approv./Lstg Regulation	Standard		Explosion Relief	
		Exterior*	Interior		Model No	Ship Wt lb/kg	Model No	Ship Wt lb/kg
2	88/333	71 in x 42 in x 75 in 1803 mm x 1067 mm x 1905 mm	53.5 in x 29.5 in x 54 in 1359 mm x 749 mm x 1372 mm	FM,N,A,E	912020	1821/826	912021	1775/805
4	80/303	71 in x 66 in x 75 in 1803 mm x 1676 mm x 1905 mm	53.5 in x 53.5 in x 60.5 in 1359 mm x 1359 mm x 1537 mm		912040	2521/1144	912041	2475/1123
6	116/439	95 in x 66 in x 97 in 2413 mm x 1676 mm x 2464 mm	77.5 in x 53.5 in x 82.5 in 1969 mm x 1359 mm x 2096 mm		912060	3505/1590	912061	3459/1569
9	168/636	95 in x 90 in x 97 in 2413 mm x 2286 mm x 2464 mm	77.5 in x 77.5 in x 82.5 in 1969 mm x 1969 mm x 2096 mm		912090	4408/1999	912091	4344/1970
12	221/837	88 in x 119 in x 97 in 2235 mm x 3023 mm x 2464 mm	77.5 in x 101.5 in x 82.5 in 1969 mm x 2578 mm x 2096 mm		912120	5225/2370	912121	5133/2328
16	288/1090	119 in x 114 in x 97 in 3023 mm x 2896 mm x 2464 mm	101.5 in x 101.5 in x 82.5 in 2578 mm x 2578 mm x 2096 mm		912160	6193/2809	912161	6095/2765

Note: Door height on 2- and 4-drum models is 51-in (1.30-m) high and 80-in (2.03-m) high on 6- through 16-drum models. \*Dimensions include mounting plates and door hardware. In most instances, locker sizes 2- through 6-drum are available to ship via a closed container truck, which can potentially reduce freight costs as compared to flat bed shipping alternatives.



## Outdoor Safety Lockers—4-hour Fire-Rated **NEW**

*Higher fire rating—provides proximity advantage over non-combustible and 2-hour locker models*

- 3-hour fire-rated door—third party tested and labeled.
- Gravity air flow vents—UL Listed fire dampers with fusible links.
- Leakproof all welded sump.

Manufactured with fire-rated and weatherproof construction, each 4-hour locker has an FM-approved fire-rated wall and roof design and meets EPA 40 CFR, NFPA 30 and NFPA 1 regulations. Multiple layers of fire-resistant gypsum wall board are encased between exterior heavy gauge steel and interior galvanized sheet steel for maximum durability. A leakproof, all welded sump provides compliant secondary containment of hazardous liquids. Galvanized steel grate flooring removes easily for cleaning.

Gravity air flow vents include UL Listed fire dampers and fusible links for maximum safety. Hydraulic door mechanism ensures door will automatically close. Forty-two inch (1.07-m) wide door comes with UL Listed keyed lockset for security. Additional safety features include static grounding connections, anchoring plates, and NFPA 704 diamond decal.

Designed to be placed within close proximity of existing structures and/or property set-backs, 4-hour fire-rated lockers provide a safe yet convenient storage solution. This proximity advantage over non-combustible and 2-hour lockers allows for the most efficient use, distribution and storage of your hazardous chemicals and drums of flammable liquids. NOTE: Please check with your local authority having jurisdiction for setback requirements and the correct wall/roof rating needed for your application.

Lockers are also available with FM-approved explosion relief panels that release at 20 psf to reduce the damage associated with a potential explosion.



Designed for close placement to existing structures, 4-hr fire-rated lockers provide a safe and convenient storage solution.



913060  
6-drum capacity



**Get answers to frequently asked questions . . .**

Visit our website to learn more about choosing the proper locker design for your application, chemical storage guidelines, and more.

**Global Protection**

Justrite products are available worldwide. For pricing and availability, simply contact the authorized distributor nearest you.



55-Gal. Drum Capacity	Sump Capacity Gallons/Liters	Dimensions W x D x H		Approv/Lstg Regulation	Standard		Explosion Relief	
		Exterior*	Interior		Model No	Ship Wt lb/kg	Model No	Ship Wt lb/kg
2	75/284	71 in x 42 in x 75 in 1803 mm x 1067 mm x 1905 mm	50.5 in x 26.5 in x 52.5 in 1283 mm x 673 mm x 1334 mm	FM,N,A,E	913020	2200/998	913021	2065/937
4	71/269	71 in x 66 in x 75 in 1803 mm x 1676 mm x 1905 mm	50.5 in x 50.5 in x 59 in 1283 mm x 1283 mm x 1499 mm		913040	3036/1377	913041	2901/1316
6	105/397	95 in x 66 in x 97 in 2413 mm x 1676 mm x 2464 mm	74.5 in x 50.5 in x 81 in 1892 mm x 1283 mm x 2057 mm		913060	4330/1964	913061	4195/1903
9	155/587	95 in x 90 in x 97 in 2413 mm x 2286 mm x 2464 mm	74.5 in x 74.5 in x 81 in 1892 mm x 1892 mm x 2057 mm		913090	5467/2480	913091	5270/2390
12	205/776	88 in x 119 in x 97 in 2235 mm x 3023 mm x 2464 mm	74.5 in x 98.5 in x 81 in 1892 mm x 2502 mm x 2057 mm		913120	6468/2934	913121	6198/2811
16	272/1030	119 in x 114 in x 97 in 3023 mm x 2896 mm x 2464 mm	98.5 in x 98.5 in x 81 in 2502 mm x 2502 mm x 2057 mm		913160	7740/3511	913161	7475/3391

Note: Door height on 2- and 4-drum models is 51-in (1.30-m) high and 80-in (2.03-m) high on 6- through 16-drum models. \*Dimensions include mounting plates and door hardware.

In most instances, locker sizes 2- through 6-drum are available to ship via a closed container truck, which can potentially reduce freight costs as compared to flat bed shipping alternatives.


## Outdoor Safety Lockers – Optional Accessories **NEW**

Accessorize your locker with options that improve function and add convenience


Customize your locker to meet specific applications with a variety of optional features and accessories designed to meet code and increase safety.

- Add sturdy steel ramps to simplify loading or unloading heavy drums with a drum dolly.
- Add galvanized steel shelving for organized, easy access to smaller containers.
- Add heating and/or air conditioning where comfort, chemical stability or freeze protection is a concern.
- Choose from two varieties of fire protection – fuse linked extinguishers or an integral dry chemical system.

Use the descriptions below, combined with the charts on the next page, to determine the accessories available with each style of safety locker.




**Grounding Kit  
Model 915505**  
Kit comes with rod – 5/8-in (16-mm) diameter x 8-ft (2438-mm) L, wire and connector



**Loading Ramp**  
Steel with anti-skid yellow paint  
• **Model 915001:**  
48-in (1219-mm) W x 120-in (3048-mm) L  
• **Model 915003:**  
48-in (1219-mm) W x 88-in (2235-mm) L



**Shelving  
Models 915101 - 915105**  
Galvanized steel shelving. Two-tier, 16-in (406-mm) wide with mounting brackets—back wall only  
Not available on locker models with explosion relief panels. Shelf package for 2- and 4-drum models (915101) will limit the ability to load locker to full drum capacity.



**Fiberglass Grate with Sump Liner  
Models 915201 - 915211**  
High density polyethylene (HDPE) sump liner and fiberglass grate flooring for acid and corrosive chemical spill resistance



**Basic Fire Protection System  
Models 915401 Model 915403**  
BC Type, FE-227 extinguisher unit, ceiling mounted and fuse linked



**Dry Chemical Fire Suppression System  
Model 915405**  
• FM-approved, UL Listed, ABC Type, dry chemical system with agent cylinder  
• One pull station and means of remote annunciation



**Interior Light and Fan Package  
Model 915501**  
• Interior explosion-proof light with exterior on/off switch — UL listed  
• Explosion-proof mechanical ventilator tied to light switch for forced vapor removal  
• Explosion-proof conduit and wiring with seal-offs



**Exterior Light  
Model 915503**  
Explosion-proof and photocell activated  
Only available when ordered with Interior Light/Fan Package 915501.



**Explosion-Proof Wall-mounted Heaters**  
• **Model 915301:** 6,000 btu  
• **Model 915303:** 12,000 btu  
Must be ordered in conjunction with the equivalent size R-11 insulation package.



**Explosion-Proof Air Conditioner**  
• **Model 915305:** 15,000 btu  
• **Model 915307:** 20,000 btu  
Must be ordered in conjunction with the equivalent size R-11 insulation package.



**Explosion Proof Wall-mounted Heater / Air Conditioner Package**  
• **Model 915309:** 6,000 / 15,000 btu  
• **Model 915311:** 12,000 / 20,000 btu  
Must be ordered in conjunction with the equivalent size R-11 insulation package.



**R-11 Insulation  
Models 915601 - 915611**  
R-11 insulation in the ceiling, walls, and sump walls for added temperature control and use in conjunction with the air and heat packages

## Optional accessories for Outdoor Safety Lockers **NEW**

### NON-COMBUSTIBLE OUTDOOR SAFETY LOCKERS

Locker Capacity	Grounding Kit		Loading Ramp		Galvanized Steel* Shelving - 2 Tier		Fiberglass † Grate Flooring (with Sump Liner)		Basic Fire † Protection System		Dry Chemical Fire † Suppression		Interior Light † and Fan Electrical Package		Exterior Light †** Package		
	Model No	Weight lb/kg	Model No	Weight lb/kg	Model No	Weight lb/kg	Model No	Weight lb/kg	Model No	Weight lb/kg	Model No	Weight lb/kg	Model No	Weight lb/kg	Model No	Weight lb/kg	
2-drum	915505	10/5	915001	300/136	915101	69/29	—	—	915401	12/5	NA	—	915501	100/45	915503	25/11	
4-drum																	915201
6-drum			915003	225/102	915103	86/39			915205	915403	35/16	915405					200/91
9-drum									915207								
12-drum									915209								
16-drum									915211								

Note: Due to space constraints in the 2- and 4-drum models, shelving and interior light packages cannot be ordered together.

### AGRI-TURF™ OUTDOOR SAFETY LOCKERS

Locker Capacity Cubic Feet/meters	Grounding Kit		Loading Ramp		Fiberglass † Grate Flooring (with Sump Liner)		Basic Fire † Protection System		Dry Chemical † Fire Suppression		Explosion- † Proof Heater		Explosion-Proof † Air Conditioner		Heater and † Air Conditioner Package		
	Model No	Weight lb/kg	Model No	Weight lb/kg	Model No	Weight lb/kg	Model No	Weight lb/kg	Model No	Weight lb/kg	Model No	Weight lb/kg	Model No	Weight lb/kg	Model No	Weight lb/kg	
49/1.4	915505	10/5	915001	300/136	915201	—	915403	35/16	915401	12/5	NA	—	NA	—	NA	—	
100/2.8																	915203
202/5.7			915003	225/102	915207	—			915405	200/91	915301	100/45	915305	200/91	915309	275/125	
292/8.3																	915209
382/10.8																	915211
500/14.2																	915311

### 2 HOUR FIRE-RATED OUTDOOR SAFETY LOCKERS

### 4 HOUR FIRE-RATED OUTDOOR SAFETY LOCKERS

Locker Capacity	Grounding Kit		Loading Ramp		Galvanized Steel* Shelving - 2 Tier		Fiberglass † Grate Flooring (with Sump Liner)		Basic Fire † Protection System		Dry Chemical † Fire Suppression		Interior Light † and Fan Electrical Package		Exterior Light †** Package		
	Model No	Weight lb/kg	Model No	Weight lb/kg	Model No	Weight lb/kg	Model No	Weight lb/kg	Model No	Weight lb/kg	Model No	Weight lb/kg	Model No	Weight lb/kg	Model No	Weight lb/kg	
2-drum	915505	10/5	915001	300/136	915101	62/29	—	—	915401	12/5	NA	—	915501	100/45	915503	25/11	
4-drum																	915201
6-drum			915003	225/102	915103	86/39			915205	915403	35/16	915405					200/91
9-drum									915207								
12-drum									915209								
16-drum									915211								

Note: Due to space constraints in the 2- and 4-drum models, shelving and interior light packages cannot be ordered together.

### Fire-Rated Models (continued)

Locker Capacity	Explosion- † Proof Heater		Explosion-Proof † Air Conditioner		Heater and † Air Conditioner Package		R-11 Insulation †	
	Model No	Weight lb/kg	Model No	Weight lb/kg	Model No	Weight lb/kg	Model No	Weight lb/kg
2-drum	NA	—	NA	—	NA	—	915601	56/25
4-drum							915603	73/33
6-drum	915301	100/45	915305	200/91	915309	275/125	915605	114/52
9-drum							915607	137/62
12-drum	915303	100/45	915307	200/91	915311	275/125	915609	160/73
16-drum							915611	185/84



**Global Protection**  
 Justrite products are available worldwide.  
 For pricing and availability, simply contact  
 the authorized distributor nearest you.

Note: Heating and air conditioning packages must be ordered in conjunction with the equivalent size insulation package on fire-rated lockers

† These accessories must be purchased in conjunction with a locker to ensure proper installation and to retain FM approval.

\* Shelving is not available on models with explosion relief panels. Shelf package for 2- and 4-drum models (915101) will limit the ability to load locker to full capacity.

\*\* Exterior light package is only available when ordered with the interior light/fan package 915501